



“What Ever It Takes”

Phone: 570-883-7005

Fax: 570-883-7006

Email: Sales@EPowerRail.com
WWW.EPowerRail.Com



Carrier AC Air Conditioner & Heater

- Only 90 lbs.
- 12 1/2 " high
- Fits any RV 14" x 14" vent
- 13,500 BTU / 15,000 BTU
- 2 speed and thermostat
- Center cooling and oscillating rear vent
- Draws only 13.5 / 15.0 amps
- Heat Pump Model 15,000 BTU heat & Cool
- NEW LOW PROFILE CARRIER
- 7.5" High 27" Wide 42" long



- Total nominal power of 5000 VA continuous on two 2500 VA AC outlets.
- Efficiency of 85% minimum at nominal rating.
- Natural convection cooling.
- Non-polarized unit
- Suited for loads requiring high inrush current
- DC input and AC output status indicator
- Waterproof and dustproof unit suitable for outdoor mounting
- Independent operation on each 2500 VA output
- Extensive protection
- Designed to meet IEC 571 standards
- Input voltage: 74 Vdc nominal
- Output voltage: 2 x 2500VA continuous independent 120 Vac outlets
- Frequency: 60 Hz \pm 0.05% Hz
- Waveform: **True sine wave** (THD < 5%)
- Operating temperatures: -40°F to 158°F (-40°C to 70°C)
- Dimensions: 24.3"H x 16.5"W x 12"D
- Weight: 160lb (72.5 kg)